Corporate Series

Boundless Imagination

600x1200mm

TECHNICAL **SPECIFICATION**



LONG DURABILITY



EASY TO CLEAN



IMPACT RESISTANCE



HYGIENIC SURFACE



FROST RESISTANCE



LOW WATER ABSORPTION



DIMENSIONAL STABILITY



EASY INSTALLATION



FIRE RESISTANCE



CHEMICAL RESISTANCE



THERMAL RESISTANCE



CRAZING RESISTANCE

SUITABLE **APPLICATIONS**



RESIDENTIAL



COMMERCIAL BUILDING



HOTEL, RESTAURANT



HOSPITAL



GYMNASIUM



HALL & CORRIDOR



MALL & SUPER MARKET



INDUSTRY



AIRPORT



SCHOOL, COLLEGE



SPA



RELIGIOUS PLACE

600x1200mm

Corporate Series

Strength in Every Surface

From design to durability, our tiles embody strength at every level. Engineered with advanced materials and precision, they provide long-lasting performance for residential, commercial, and corporate spaces.

600x1200mm

INDEX

ASCOLANO BLANCO


ASCOLANO BONE


AURELIO MATRIX GREY


BOLGHERI WHITE

CARONIA ONYX

CLASSIC TRAVERTINE

FERRAGA CAMELLO


FERRAGA MOCHA

LUMINOUS BEIGE

OPAL DORATA


ROXAS SAND


SILENT STONE


SNOWFALL LUXE

TAJ DIAMOND

VERSAILLE CORD


VERSAILLE SUEDE


WELKIN ONYX

Corporate Series

ASCOLANO BLANCO

Endmatch Random-06

Available Finish









Corporate Series



ASCOLANO BONE

Endmatch Random-06

Available Finish









Corporate Series



AURELIO MATRIX GREY

Endmatch Random-04

Available Finish











BOLGHERI WHITE

Endmatch Random-04

Available Finish









Corporate Series



CARONIA ONYX

Endmatch Random-04

Available Finish









CLASSIC TRAVERTINE

Random-05

Available Finish











FERRAGA CAMELLO

Endmatch Random-03

Available Finish









Corporate Series



FERRAGA MOCHA

Endmatch Random-03

Available Finish











LUMINOUS BEIGE

Endmatch Random-03

Available Finish









OPAL DORATA

Endmatch Random-04

Available Finish











ROXAS SAND

Endmatch Random-04

Available Finish











SILENT STONE

Random-04

Available Finish











SNOWFALL LUXE

Endmatch Random-04

Available Finish









TAJ DIAMOND

Endmatch Random-03

Available Finish









Corporate Series

VERSAILLE CORD

Endmatch Random-04

Available Finish











VERSAILLE SUEDE

Endmatch Random-04

Available Finish









Corporate Series



WELKIN ONYX

Endmatch Random-04

Available Finish









CLEANING & MAINTENANCE

Our products are non porous (due to their high quality raw materials, stringent production parameters and state of the art technology), hence any dust or deposited waste cannot penetrate the surface.

For most cases only a damp cloth is sufficient for cleaning.

Regular cleaning highlights the aesthetic features of the surface and gives it exceptional shine.

For highly aggressive cleaning caused by some common food and substances follow the table below.

TYPE OF STAIN	CHEMICAL PRODUCT	EXAMPLE
Grease	Alkaline - Solvent	Detergent
Oil	Solvent	Ammonia, Baking Soda
Ink	Oxidant - Solvent	Alcohol, Liquid Bleach, Nail Paint Remover
Rust	Acid	Hydrochloric Acid, Vinegar, Red Harpic
Lime	Acid	Descaling Agents, Hydrochloric Acid
Cement	Acid	Hydrochloric Acid
Wine	Alkaline	Ammonia, Liquid Bleach
Coffee	Alkaline - Solvent	Ammonia, Liquid Bleach
Rubber	Solvent	Alcohol, Thinner
Plaster	Acid	Hydrochloric Acid
Candle Wax	Solvent	Alcohol, Thinner
Iodine	Oxidant	Liquid Bleach
Blood	Oxidant	Liquid Bleach
Ice Cream	Alkaline	Liquid Bleach

Note: It is recommended that any kind of stain needs to be cleaned immediately, as soon as possible.

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	STANDARD AS PER ISO-13006/2018 En14411 gr.bla	**MOTTO VALUE**	TEST METHOD
Regulatory Properties			
Deviation in Length & Width	+0.5%	+0.2%	ISO 10545-2
Deviation in Thickness	+5%	+5%	ISO 10545-2
Straightness of Sides	+0.5%	+0.2%	ISO 10545-2
Rectangularity	+0.5%	+0.2%	ISO 10545-2
Surface Flatness	+0.5%	+0.3%	ISO 10545-2
Colour Difference	ΔE<1.00	ΔE<0.30	ISO 10545-16
Glossiness	As per Mfg.	>90%	Gloss Meter 60°
Structural Properties			
Water Absorption	<0.5 %	<0.3%	ISO 10545-3
Apparent Density	As Per Mfg.	>2.20 g/cc	ISO 10545-3
Massive Mechanical Properties			
Modulus of Repture	Min.35N/mm^2	Min.40N/mm^2	ISO 10545-4
Breaking Strength	Min. 1300 N	Min. 2000 N	ISO 10545-4
Impact Resistance	As per Mfg.	Min. 0.55	ISO 10545-4
Surface Mechanical Properties			
Surface Abrasion Resistance	As per Mfg.	Min. class 3	ISO 10545-7
Mohs Hardness	As per Mfg.	Min. class 4	BS EN 15771
Thermo Hygrometric Properties			
Frost Resistance	As Per Mfg.	Frost Proof	ISO 10545-12
Thermal Shock Resistance	Min. 10 Cycle	Min. 10 Cycle	ISO 10545-9
Moisture Expansion	Max. 0.6mm/m	Max. 0.02mm/m	ISO 10545-10
Thermal Expansion	Max. 9.0 x 10^{-6}	Max. 6.0x10^{-6}	ISO 10545-8
Chemical Properties			
Chemical Resistance	As Per Mfg.	No Damage	ISO 10545-13
Stain Resistance	Resistant	Resistant	ISO 10545-14
Safety Properties			
Slip Resistance	As per Mfg.	N. A.	DIN 51130
Fire Resistance	As per Mfg.	Fire Proof	N. A.

PACKING DETAILS

Dimension (mm)	No. of Pcs/Box	Square Feet
600x1200mm	2 Pcs.	15.5 Sq. ft