URBAN COLLECTION

GLAZED PORCELAIN TILES

200X200MM (MATT)

URBAN

COLLECTION

This collection consists of a wide range of 13 awesome patterns and comes in 5 base colors that suit every taste and can be suitable for any space. It comes in a gracious matt finish and elegant 200x200mm size.





URBAN
COLLECTION

GLAZED PORCELAIN TILES
WITH LOW WATER ABSORTION E≤0.5%





SP 80013
URBAN NAPLES





SP 80014
URBAN APOPKA





SP 80015
URBAN
MARIANNA





SP 80016
URBAN
BELLEVUE

SIZE.
200X200MM

SURFACE
MATT

WALL TILE

FLOOR TILE



SP 80013
URBAN NAPLES




SP 80014
URBAN APOPKA

SP 80015
URBAN MARIANNA

URBAN
COLLECTION

GLAZED PORCELAIN TILES
WITH LOW WATER ABSORTION E≤0.5%





SP 80017
URBAN
CLEARWATER





SP 80018
URBAN
LAUDERHILL





SP 80019
URBAN
PAHOKEE





SP 80020
URBAN PARKER

SIZE.
200X200MM

SURFACE
MATT

WALL TILE

FLOOR TILE

SP 80020
URBAN PARKER

URBAN
COLLECTION

GLAZED PORCELAIN TILES
WITH LOW WATER ABSORTION E≤0.5%





SP 80022
URBAN OCALA





SP 80024
URBAN
LABELLE





SP 80025
URBAN
DAYTONA





SP 80026
URBAN MIAMI

SIZE.
200X200MM

SURFACE
MATT

WALL TILE

FLOOR TILE

URBAN
COLLECTION

GLAZED PORCELAIN TILES
WITH LOW WATER ABSORTION E≤0.5%

SP 80027
URBAN IVORY





SP 80028
URBAN BEIGE





SP 80029
URBAN BROWN





SP 80030
URBAN BLACK

SIZE.
200X200MM

SURFACE
MATT

WALL TILE

FLOOR TILE

SP 80029
URBAN BROWN

URBAN
COLLECTION

GLAZED PORCELAIN TILES
WITH LOW WATER ABSORTION E≤0.5%





SP 80031
URBAN
SKY BLUE





SP 80032
URBAN
HAMPTON

SIZE.
200X200MM

SURFACE
MATT

WALL TILE

FLOOR TILE

SP 80032
URBAN HAMPTON

CHARACTERISTICS OF GLAZED PORCELAIN TILES

DRY-PRESSED CERAMIC TILES, WITH LOW WATER ABSORTION ≤0.5%,
FOR INTERNAL AND EXTERNAL WALLS AND FLOORS

Fire Reaction	Class A1
Breaking Strength	≥1300 N
Thermal Shock Resistance	PASS
Durability For:	
Indoor Uses	PASS
Outdoor Uses	PASS
Frost Resistance	PASS
Resistance to Chemical for Household use and Swimming Pool Salts	ISO 10545-13 GA
Resistance to Low Concentrations of Acids and Alkalis	ISO 10545-13 GLA
Resistance to High Concentrations of Acids and Alkalis	ISO 10545-13 GHA
Stain Resistance	ISO 10545-14 Class 5

PACKAGING DETAILS

SIZE	THICKNESS	PIECES/BOX	SQM./BOX	SQFT./BOX	KG/BOX
200X200MM (8"X8")	8.00MM	19	0.76	8.18	14.00

Note :

- Size / shade variation is inherent in porcelain tiles , in case of any complain its should be brought to our dealer's notice before laying the tiles.
- Colour shown are indicative only. Check actual tiles for exact colour.
- The information contained in this catalogue are accurate as possible, but cannot be considered as legally binding.
- Customers are advised to inspect a sample of the tile before ordering.
- The company reserves the right to change the specifications without prior notice.

Exterior Elevation or interior Walls & Floors



TILE FIXING INSTRUCTIONS

It is necessary to use an appropriate adhesive and grouting material for each product An initial approach must be made before starting the installation and take into account the type of joint, structural, perimeter, expansion and installation that must be used for each use. We advise that to obtain an optimal result a 1.5 mm joint should be used

Once the placement is finished: it is recommended to remove the remains of adhesive material and specific grouting for each material, following the manufacturer's instructions for these products.

In general, powder detergents and aggressive scouring pads should not be used for cleaning. It is enough to clean the tiles with a sponge, warm water and a neutral liquid soap. Finally, rinse with clean water.